

/ SEPARATING

# Komptech Ballistor

BALLISTIC WASTE SEPARATOR



MASTER DISTRIBUTOR OF KOMPTECH

Ballistic is short for put air and gravity on the clock.



**This electric-drive waste separator screens and separates 2D, 3D, and fines fractions in a single process, maximizing material sorting and recovery downstream.**

## / QUICK STATS

- Process C&D debris, MSW, organics waste and single-stream recyclables
- 2D materials shake free of unwanted fines as the 3D material rolls downward, with all fractions separated
- Separate recyclables from waste in one process

The Komptech Ballistor is available in four model sizes with multiple configurable options to meet your operation's unique performance needs:



## KOMPTECH BALLISTOR / Technical Specifications

Machine Model	BALLISTOR 10300	BALLISTOR 8300	BALLISTOR 6300	BALLISTOR 4300
<b>Power</b>				
Electrical Power:	11 kW / 14.7 HP	11 kW / 14.7 HP	5.5 kW / 7.4 HP	5.5 kW / 7.4 HP
<b>Proportion</b>				
Machine Length:	24'6"	24'6"	24'6"	24'6"
Machine Width:	16'3"	13'5"	10'8"	7'10"
Weight:	~19,500 lbs	~17,000 lbs	~14,000 lbs	~11,500 lbs
<b>Performance (dependent on material)</b>				
Number of Fractions:	3	3	3	3
Number of Screening Paddles:	10	8	6	4
Length of Screening Paddles:	18'4"	18'4"	18'4"	18'4"
Screening Area:	28.6 yd <sup>2</sup>	23 yd <sup>2</sup>	17.2 yd <sup>2</sup>	11.5 yd <sup>2</sup>
Maximum Throughput:	~209 yd <sup>3</sup> /hr (~161 m <sup>3</sup> /hr)	~170 yd <sup>3</sup> /hr (~130 m <sup>3</sup> /hr)	~131 yd <sup>3</sup> /hr (~99 m <sup>3</sup> /hr)	~79 yd <sup>3</sup> /hr (~61 m <sup>3</sup> /hr)

Think Viably for industry expertise, world-class products, parts, service, and support.

Wherever you work.



CONSTRUCTION AND DEMOLITION (C&D)



MUNICIPAL SOLID WASTE (MSW)



ORGANICS WASTE



SINGLE-STREAM RECYCLING



Scan to see the Ballistor in action >

